

# FLR91X-A

低压汽车电线

-40℃~+150℃/3000h

Low-tension cables for automobiles



**产品特点:**

薄壁，耐热

**导体:**

导体由软圆铜线绞合而成。

**绝缘材料:**

辐照交联聚烯烃

**执行标准:**

ISO 6722 Class D

**包装方式:** 成圈，成箱，成盘，成桶。

**FEATURE:**

Thin-walled , Hear-resistant

**CONDUCTOR:**

The conductor was stranded with soft-annealed copper

**INSULATION:**

XLPO

**STANDARD:**

ISO 6722 Class D

FORM OF DELIVERY: On reels, boxes, drums, barrels.

导体/Conductor					电线/Cable	
标称截面 Nominal Cross-section mm <sup>2</sup>	结 构 Number of single wires/ Max. dia. of strand Pcs/mm	最大电阻 Resistance (20℃) mΩ/m		最大外径 Outside diameter mm	最小厚度 Insulation thickness Min. mm	最大外径 Outside Diameter Max. mm
		Brae	Tnned			
0.35	7/0.27	54.4	55.5	0.90	0.20	1.30
0.50	19/0.19	37.1	38.2	1.10	0.22	1.60
0.75	19/0.24	24.7	25.4	1.30	0.24	1.90
1.0	19/0.27	18.5	19.1	1.50	0.24	2.10
1.5	19/0.33	12.7	13.0	1.80	0.24	2.40
2.0	19/0.38	9.42	9.69	2.00	0.28	2.80
2.5	19/0.41	7.60	7.82	2.20	0.28	3.00



北京斯普乐电线电缆有限公司  
Beijing S.P.L Wire & Cable Co.,Ltd

Tel: 86-10-61665369  
Fax: 86-10-61667272  
Web: www.spl-cable.com

# FLR91X-B

低压汽车电线

-40℃~+150℃/3000h

Low-tension cables for automobiles



**产品特点:**

薄壁, 耐热

**导体:**

导体由软圆铜线或镀锡软圆铜线绞合而成。

**绝缘材料:**

辐照交联聚烯烃

**执行标准:**

ISO 6722 Class D

**包装方式:** 成圈, 成箱, 成盘, 成桶。

**FEATURE:**

Thin-walled, Heat-resistant

**CONDUCTOR:**

The conductor was stranded with bare/tinned soft-annealed copper

**INSULATION:**

XLPO

**STANDARD:**

ISO 6722 Class D

FORM OF DELIVERY: On reels, boxes, drums, barrels.

导体/Conductor				电线/Cable		
标称截面 Nominal Cross-section mm <sup>2</sup>	结构 Number of single wires/ Max. dia. of strand Pcs/mm	最大电阻 Resistance (20℃) mΩ/m Bare Tinned		最大外径 Outside diameter mm	最小厚度 Insulation thickness Min. mm	最大外径 Outside Diameter Max. mm
0.35	12/0.21	54.4	55.5	0.90	0.20	1.40
0.50	16/0.21	37.1	38.2	1.10	0.22	1.60
0.75	24/0.21	24.7	25.4	1.30	0.24	1.90
1.0	32/0.21	18.5	19.1	1.50	0.24	2.10
1.5	30/0.26	12.7	13.0	1.80	0.24	2.40
2.0	28/0.31	9.42	9.69	2.00	0.28	2.80
2.5	50/0.26	7.60	7.82	2.20	0.28	3.00
3	44/0.31	6.15	6.36	2.40	0.32	3.40
4	56/0.31	4.71	4.85	2.80	0.32	3.70
5	70/0.31	3.94	4.02	3.10	0.32	4.20
6	84/0.31	3.14	3.23	3.40	0.32	4.30
10	80/0.41	1.82	1.85	4.50	0.48	6.00
16	126/0.41	1.16	1.18	6.30	0.52	7.90
25	196/0.41	0.743	0.757	7.80	0.52	9.40



北京斯普乐电线电缆有限公司  
Beijing S.P.L Wire & Cable Co., Ltd

Tel: 86-10-61665369  
Fax: 86-10-61667272  
Web: www.spl-cable.com