

**产品特点:**

特殊壁厚，耐热

**导体:**

导体由软圆铜线绞合而成。

**绝缘材料:**

交联聚烯烃

**执行标准:**

SAE J1128

**包装方式:** 成圈，成箱，成盘，成桶。**FEATURE:**

Special purpose , Heat-resistant

**CONDUCTOR:**

The conductor was stranded with soft-annealed copper

**INSULATION:**

XLPO

**STANDARD:**

SAE J1128

**FORM OF DELIVERY:** On reels, boxes, drums, barrels.

导体/Conductor				电线/Cable	
线规号 AWG	标称截面 Nominal Cross-section mm <sup>2</sup>	结 构 Number of single wires/ dia. of strand Pcs/mm	最小截面 Minimum Area mm <sup>2</sup>	最小厚度 Insulation thickness Min. mm	最大外径 Outside Diameter Max. mm
20	0.5	7/0.32	0.508	0.52	2.80
18	0.8	19/0.23	0.760	0.53	3.00
16	1	19/0.28	1.12	0.57	3.40
14	2	19/0.36	1.85	0.62	3.90
12	3	19/0.45	2.91	0.66	4.60
10	5	19/0.57	4.65	0.73	5.30
8	8	19/0.71	7.23	0.76	6.20